



## TFT LCD Approval Specification

# MODEL NO.: V420B1 - L01

Customer: \_\_\_\_\_

Approved by: \_\_\_\_\_

Note:

|             |                  |  |
|-------------|------------------|--|
| Approved By | TV Head Division |  |
|             | LY Chen          |  |

|             |           |                          |
|-------------|-----------|--------------------------|
| Reviewed By | QRA Dept. | Product Development Div. |
|             | Tomy Chen | WT Lin                   |

|             |                                              |          |
|-------------|----------------------------------------------|----------|
| Prepared By | LCD TV Marketing and Product Management Div. |          |
|             | Ken Wu                                       | CY Chang |

## CONTENTS

|                                                                  |    |
|------------------------------------------------------------------|----|
| REVISION HISTORY .....                                           | 4  |
| 1. GENERAL DESCRIPTION .....                                     | 5  |
| 1.1 OVERVIEW .....                                               | 5  |
| 1.2 FEATURES .....                                               | 5  |
| 1.3 APPLICATION .....                                            | 5  |
| 1.4 GENERAL SPECIFICATIONS .....                                 | 5  |
| 1.5 MECHANICAL SPECIFICATIONS .....                              | 6  |
| 2. ABSOLUTE MAXIMUM RATINGS .....                                | 7  |
| 2.1 ABSOLUTE RATINGS OF ENVIRONMENT .....                        | 7  |
| 2.2 ELECTRICAL ABSOLUTE RATINGS .....                            | 8  |
| 2.2.1 TFT LCD MODULE .....                                       | 8  |
| 2.2.2 BACKLIGHT INVERTER UNIT .....                              | 8  |
| 3. ELECTRICAL CHARACTERISTICS .....                              | 9  |
| 3.1 TFT LCD MODULE .....                                         | 9  |
| 3.2 BACKLIGHT UNIT .....                                         | 11 |
| 3.2.1 CCFL (Cold Cathode Fluorescent Lamp) CHARACTERISTICS ..... | 11 |
| 3.2.2 INVERTER CHARACTERISTICS .....                             | 11 |
| 3.2.3 INVERTER INTERFACE CHARACTERISTICS .....                   | 13 |
| 4. BLOCK DIAGRAM OF INTERFACE .....                              | 14 |
| 4.1 TFT LCD MODULE .....                                         | 14 |
| 5. INPUT TERMINAL PIN ASSIGNMENT .....                           | 15 |
| 5.1 TFT LCD Module Input .....                                   | 15 |
| 5.2 BACKLIGHT UNIT .....                                         | 16 |
| 5.3 INVERTER UNIT .....                                          | 17 |
| 5.4 BLOCK DIAGRAM OF INTERFACE .....                             | 19 |
| 5.5 LVDS INTERFACE .....                                         | 20 |
| 5.6 COLOR DATA INPUT ASSIGNMENT .....                            | 21 |
| 6. INTERFACE TIMING .....                                        | 22 |
| 6.1 INPUT SIGNAL TIMING SPECIFICATIONS .....                     | 22 |
| 6.2 POWER ON/OFF SEQUENCE .....                                  | 24 |

**CHI MEI**  
OPTOELECTRONICS CORP.Issue Date: Sep.22.2007  
Model No.: V420B1-L01**Approval**

|                                             |    |
|---------------------------------------------|----|
| 7. OPTICAL CHARACTERISTICS .....            | 25 |
| 7.1 TEST CONDITIONS.....                    | 25 |
| 7.2 OPTICAL SPECIFICATIONS .....            | 25 |
| 8. PRECAUTIONS.....                         | 29 |
| 8.1 ASSEMBLY AND HANDLING PRECAUTIONS ..... | 29 |
| 8.2 SAFETY PRECAUTIONS .....                | 29 |
| 9. DEFINITION OF LABELS.....                | 30 |
| 9.1 CMO MODULE LABEL .....                  | 30 |
| 10. PACKAGING.....                          | 31 |
| 10.1 PACKAGING SPECIFICATIONS .....         | 31 |
| 10.2 PACKAGING METHOD.....                  | 31 |
| 11. MECHANICAL CHARACTERISTICS .....        | 33 |

**CHI MEI**  
OPTOELECTRONICS CORP.

Issue Date: Sep.22.2007

Model No.: V420B1-L01

**Approval****REVISION HISTORY**

| Version | Date       | Page<br>(New) | Section    | Description                                                     |
|---------|------------|---------------|------------|-----------------------------------------------------------------|
| Ver.2.0 | Jan.12.'07 | All           | All        | Approval Specification was first issued.                        |
| Ver.2.1 | Jun.20.'07 | 24            | 6.2        | T4 range needs to be corrected on Power On/Off Sequence figure. |
| Ver.2.2 | Sep.22.'07 | 32<br>33~35   | 10.2<br>11 | Packaging method<br>Change ME design                            |

## 1. GENERAL DESCRIPTION

### 1.1 OVERVIEW

V420B1-L01 is a 42" TFT Liquid Crystal Display module with 16-CCFL Backlight unit and 1ch-LVDS interface.

This module supports 1366 x 768 HDTV format and can display true 16.7M colors (8-bit/color). The inverter module for backlight is built-in.

### 1.2 FEATURES

- High brightness (500 nits)
- High contrast ratio (1500:1)
- Dynamic contrast ratio (6000:1)
- Fast response time (Gray to gray average 6.5 ms)
- High color saturation (NTSC 72%)
- HDTV (1366 x 768 pixels) resolution, true HDTV format
- DE (Data Enable) only mode
- LVDS (Low Voltage Differential Signaling) interface
- Optimized response time for 60 Hz frame rate
- Ultra wide viewing angle : Super MVA technology
- 180 degree rotation display option
- RoHS compliance

### 1.3 APPLICATION

- Standard Living Room TVs.
- Public Display Application.
- Home Theater Application.
- MFM Application.

### 1.4 GENERAL SPECIFICATIONS

| Item                   | Specification                              | Unit  | Note |
|------------------------|--------------------------------------------|-------|------|
| Active Area            | 930.246(H) x 523.008 (V) (42.02" diagonal) | mm    | (1)  |
| Bezel Opening Area     | 939 (H) x 531 (V)                          | mm    |      |
| Driver Element         | a-si TFT active matrix                     | -     | -    |
| Pixel Number           | 1366 x R.G.B. x 768                        | pixel | -    |
| Pixel Pitch(Sub Pixel) | 0.227 (H) x 0.681 (V)                      | mm    | -    |
| Pixel Arrangement      | RGB vertical stripe                        | -     | -    |
| Display Colors         | 16.7M                                      | color | -    |
| Display Operation Mode | Transmissive mode / Normally black         | -     | -    |
| Surface Treatment      | Anti-Glare coating (Haze 25%)              | -     | (2)  |

Note (1) Please refer to the attached drawings in chapter 9 for more information about the front and back outlines.

Note (2) The spec. of the surface treatment is temporarily for this phase. CMO reserves the rights to change this feature.

**1.5 MECHANICAL SPECIFICATIONS**

| Item        |                | Min.  | Typ.  | Max.  | Unit | Note     |
|-------------|----------------|-------|-------|-------|------|----------|
| Module Size | Horizontal (H) | 982.0 | 983.0 | 984.0 | mm   | (1), (2) |
|             | Vertical (V)   | 575.0 | 576.0 | 577.0 | mm   |          |
|             | Depth (D)      | 53.5  | 54.5  | 55.5  | mm   |          |
| Weight      |                | 12300 | 12500 | 12700 | g    | -        |

Note (1) Please refer to the attached drawings for more information of front and back outline dimensions.

Note (2) Module Depth does not include connectors.

## 2. ABSOLUTE MAXIMUM RATINGS

### 2.1 ABSOLUTE RATINGS OF ENVIRONMENT

| Item                          | Symbol | Value |      | Unit | Note     |
|-------------------------------|--------|-------|------|------|----------|
|                               |        | Min.  | Max. |      |          |
| Storage Temperature           | TST    | -20   | +60  | °C   | (1)      |
| Operating Ambient Temperature | TOP    | 0     | 50   | °C   | (1), (2) |
| Shock (Non-Operating)         | SNOP   | -     | 50   | G    | (3), (5) |
| Vibration (Non-Operating)     | VNOP   | -     | 1.0  | G    | (4), (5) |

Note (1) Temperature and relative humidity range is shown in the figure below.

(a) 90 %RH Max. ( $T_a \leq 40\text{ }^{\circ}\text{C}$ ).

(b) Wet-bulb temperature should be  $39\text{ }^{\circ}\text{C}$  Max. ( $T_a > 40\text{ }^{\circ}\text{C}$ ).


(c) No condensation.

Note (2) The maximum operating temperature is based on the test condition that the surface temperature of display area is less than or equal to  $65\text{ }^{\circ}\text{C}$  with LCD module alone in a temperature controlled chamber. Thermal management should be considered in final product design to prevent the surface temperature of display area from being over  $65\text{ }^{\circ}\text{C}$ . The range of operating temperature may degrade in case of improper thermal management in final product design.

Note (3) 11 ms, half sine wave, 1 time for  $\pm X$ ,  $\pm Y$ ,  $\pm Z$ .

Note (4) 10 ~ 200 Hz, 10 min, 1 time each X, Y, Z.

Note (5) At testing Vibration and Shock, the fixture in holding the module has to be hard and rigid enough so that the module would not be twisted or bent by the fixture.



## 2.2 ELECTRICAL ABSOLUTE RATINGS

### 2.2.1 TFT LCD MODULE

| Item                 | Symbol | Value |      | Unit | Note |
|----------------------|--------|-------|------|------|------|
|                      |        | Min.  | Max. |      |      |
| Power Supply Voltage | VCC    | -0.3  | 13.5 | V    | (1)  |
| Logic Input Voltage  | VIN    | -0.3  | 3.6  | V    |      |

### 2.2.2 BACKLIGHT INVERTER UNIT

| Item                 | Symbol | Value |      | Unit | Note     |
|----------------------|--------|-------|------|------|----------|
|                      |        | Min.  | Max. |      |          |
| Lamp Voltage         | VW     | —     | 3000 | VRMS |          |
| Power Supply Voltage | VBL    | 0     | 30   | V    | (1)      |
| Control Signal Level | —      | -0.3  | 7    | V    | (1), (3) |

Note (1) Permanent damage to the device may occur if maximum values are exceeded. Function operation should be restricted to the conditions described under Normal Operating Conditions.

Note (2) No moisture condensation or freezing.

Note (3) The control signals include On/Off Control and Internal PWM Control.



### 3. ELECTRICAL CHARACTERISTICS


#### 3.1 TFT LCD MODULE


(Ta = 25 ± 2 °C)

| Parameter                   |                                           | Symbol | Value |      |       | Unit | Note |
|-----------------------------|-------------------------------------------|--------|-------|------|-------|------|------|
|                             |                                           |        | Min.  | Typ. | Max.  |      |      |
| Power Supply Voltage        |                                           | VCC    | 10.8  | 12   | 13.2  | V    | (1)  |
| Power Supply Ripple Voltage |                                           | VRP    | -     | -    | 300   | mV   |      |
| Rush Current                |                                           | IRUSH  | -     | -    | 2.0   | A    | (2)  |
| Power Supply Current        | White                                     | -      | -     | 0.7  | 0.96  | A    | (3)  |
|                             | Black                                     | -      | -     | 0.28 | -     | A    |      |
|                             | Vertical Stripe                           | -      | -     | 0.65 | -     | A    |      |
| LVDS Interface              | Differential Input High Threshold Voltage | VLVTH  | -     | -    | 100   | mV   |      |
|                             | Differential Input Low Threshold Voltage  | VLVTL  | -100  | -    | -     | mV   |      |
|                             | Common Input Voltage                      | VLVC   | 1.125 | 1.25 | 1.375 | V    |      |
|                             | Terminating Resistor                      | RT     | -     | 100  | -     | ohm  |      |
| CMOS interface              | Input High Threshold Voltage              | VIH    | 2.7   | -    | 3.3   | V    |      |
|                             | Input Low Threshold Voltage               | VIL    | 0     | -    | 0.7   | V    |      |

Note (1) The module should be always operated within the above ranges.

Note (2) Measurement condition:



**Vcc rising time is 470us**


Note (3) The specified power supply current is under the conditions at  $V_{cc} = 12\text{ V}$ ,  $T_a = 25 \pm 2\text{ }^{\circ}\text{C}$ ,  $f_v = 60\text{ Hz}$ , whereas a power dissipation check pattern below is displayed.

a. White Pattern




Active Area

b. Black Pattern




Active Area

c. Vertical Stripe Pattern



Active Area



### 3.2 BACKLIGHT UNIT

#### 3.2.1 CCFL (Cold Cathode Fluorescent Lamp) CHARACTERISTICS

(Ta = 25 ± 2 °C)

| Parameter            | Symbol | Value  |        |      | Unit  | Note       |
|----------------------|--------|--------|--------|------|-------|------------|
|                      |        | Min.   | Typ.   | Max. |       |            |
| Lamp Input Voltage   | VL     | -      | 1490   | -    | VRMS  | -          |
| Lamp Current         | IL     | 6.0    | 6.5    | 7.0  | mARMS | (1)        |
| Lamp Turn On Voltage | VS     | -      | -      | 2370 | VRMS  | Ta = 0 °C  |
|                      |        | -      | -      | 2160 | VRMS  | Ta = 25 °C |
| Operating Frequency  | FL     | 40     | -      | 70   | KHz   |            |
| Lamp Life Time       | LBL    | 50,000 | 60,000 | -    | Hrs   | (2)        |

#### 3.2.2 INVERTER CHARACTERISTICS

(Ta = 25 ± 2 °C)

| Parameter                                  | Symbol   | Value |      |      | Unit  | Note               |
|--------------------------------------------|----------|-------|------|------|-------|--------------------|
|                                            |          | Min.  | Typ. | Max. |       |                    |
| Power Consumption at Gray level 255        | P255     | -     | 150  | 160  | W     | (5)(6), IL = 6.8mA |
| Power Consumption at Gray level 128        | P128     | -     | 75   | -    | W     | Dynamic BLU Enable |
| Power Consumption at Gray level 0          | P0       | -     | 50   | -    | W     | Dynamic BLU Enable |
| Power Supply Voltage                       | VBL      | 22.8  | 24   | 25.2 | VDC   |                    |
| Power Supply Current                       | IBL      | -     | 6.25 | -    | A     | Non Dimming        |
| Input Inrush Current                       | -        | -     | -    | 9.8  | Apeak |                    |
| Input Ripple Noise                         | -        | -     | -    | 912  | mVP-P | VBL=22.8V          |
| Oscillating Frequency<br>Dimming frequency | FW<br>FB | 47    | 50   | 53   | kHz   |                    |
|                                            |          | 150   | 160  | 170  | Hz    |                    |
| Minimum Duty Ratio                         | DMIN     | -     | 20   | -    | %     |                    |
|                                            |          |       |      |      |       |                    |
|                                            |          |       |      |      |       |                    |

Note (1) Lamp current is measured by utilizing AC current probe and its value is average by measuring master and slave board.

Note (2) The lamp starting voltage VS should be applied to the lamp for more than 1 second after startup.

Otherwise the lamp may not be turned on.


Note (3) The lamp frequency may produce interference with horizontal synchronous frequency of the display input signals, and it may result in line flow on the display. In order to avoid interference, the lamp frequency

should be detached from the horizontal synchronous frequency and its harmonics as far as possible.

Note (4) The life time of a lamp is defined as when the brightness is larger than 50% of its original value and the effective discharge length is longer than 80% of its original length (Effective discharge length is defined as an area that has equal to or more than 70% brightness compared to the brightness at the center point of lamp.) as the time in which it continues to operate under the condition at  $T_a = 25 \pm 2^\circ\text{C}$  and  $IL = 6.0 \sim 7.0\text{mA}_{\text{rms}}$ .

Note (5) The power supply capacity should be higher than the total inverter power consumption PBL. Since the pulse width modulation (PWM) mode was applied for backlight dimming, the driving current changed as PWM duty on and off. The transient response of power supply should be considered for the changing loading when inverter dimming.

Note (6) The measurement condition of Max. value is based on 42" backlight unit under input voltage 24V, average lamp current 6.8 mA and lighting 30 minutes later.




### 3.2.3 INVERTER INTERFACE CHARACTERISTICS

| Parameter                    | Symbol | Test Condition | Value |      |      | Unit | Note |
|------------------------------|--------|----------------|-------|------|------|------|------|
|                              |        |                | Min.  | Typ. | Max. |      |      |
| On/Off Control Voltage       | ON     | VBLON          | —     | 2.0  | —    | 5.0  | V    |
|                              | OFF    |                | —     | 0    | —    | 0.8  | V    |
| Internal PWM Control Voltage | MAX    | VIPWM          | —     | 3.15 | 3.3  | 3.45 | V    |
|                              | MIN    |                | —     | —    | 0    | —    | V    |
| Control Signal Rising Time   | Tr     | —              | —     | —    | 100  | ms   |      |
| Control Signal Falling Time  | Tf     | —              | —     | —    | 100  | ms   |      |
| VBL Rising Time              | Tr1    | —              | 30    | —    | 50   | ms   |      |
| VBL Falling Time             | Tf1    | —              | 30    | —    | 50   | ms   |      |
| PWM Delay Time               | TPWM   | —              | 100   | —    | 300  | mS   |      |
| Input impedance              | RIN    | —              | 1     | —    | —    | MΩ   |      |
| BLON Delay Time              | Ton    | —              | 1     | —    | —    | ms   |      |
| BLON Off Time                | Toff   | —              | 1     | —    | —    | ms   |      |


Note (1) The power sequence and control signal timing are shown in the following figure.

Note (2) The power sequence and control signal timing must follow the figure below. For a certain reason, the inverter has a possibility to be damaged with wrong power sequence and control signal timing.



## 4. BLOCK DIAGRAM OF INTERFACE

### 4.1 TFT LCD MODULE



## 5. INPUT TERMINAL PIN ASSIGNMENT

### 5.1 TFT LCD Module Input

| Pin | Name    | Description                                            | Note |
|-----|---------|--------------------------------------------------------|------|
| 1   | VCC     | +12V power supply                                      |      |
| 2   | VCC     | +12V power supply                                      |      |
| 3   | VCC     | +12V power supply                                      |      |
| 4   | VCC     | +12V power supply                                      |      |
| 5   | GND     | Ground                                                 |      |
| 6   | GND     | Ground                                                 |      |
| 7   | GND     | Ground                                                 |      |
| 8   | N.C.    | No Connection                                          | (2)  |
| 9   | SELLVDS | LVDS data format Selection                             | (3)  |
| 10  | EN_DBL  | Dynamic Backlight Enable                               | (4)  |
| 11  | GND     | Ground                                                 |      |
| 12  | RX0-    | Pixel Negative LVDS differential data input. Channel 0 |      |
| 13  | RX0+    | Pixel Positive LVDS differential data input. Channel 0 |      |
| 14  | GND     | Ground                                                 |      |
| 15  | RX1-    | Pixel Negative LVDS differential data input. Channel 1 |      |
| 16  | RX1+    | Pixel Positive LVDS differential data input. Channel 1 |      |
| 17  | GND     | Ground                                                 |      |
| 18  | RX2-    | Pixel Negative LVDS differential data input. Channel 2 |      |
| 19  | RX2+    | Pixel Positive LVDS differential data input. Channel 2 |      |
| 20  | GND     | Ground                                                 |      |
| 21  | CLK-    | Pixel Negative LVDS differential clock input.          |      |
| 22  | CLK+    | Pixel Positive LVDS differential clock input.          |      |
| 23  | GND     | Ground                                                 |      |
| 24  | RX3-    | Pixel Negative LVDS differential data input. Channel 3 |      |
| 25  | RX3+    | Pixel Positive LVDS differential data input. Channel 3 |      |
| 26  | GND     | Ground                                                 |      |
| 27  | N.C.    | No Connection                                          | (2)  |
| 28  | N.C.    | No Connection                                          |      |
| 29  | N.C.    | No Connection                                          |      |
| 30  | GND     | Ground                                                 |      |

Note (1) Connector part No: FI-X30SSL-HF (JAE) or equivalent.

Note (2) Reserved for internal use. Please leave it open.

Note (3) Low : VESA LVDS Format (default), High : JEIDA LVDS Format.

Note (4) Low : function disable (default), High : Dynamic Backlight function enable.


## 5.2 BACKLIGHT UNIT

The pin configuration for the housing and the leader wire is shown in the table below.

CN3-CN22: BHR-04VS-1 (JST).

| Pin | Name | Description  | Wire Color |
|-----|------|--------------|------------|
| 1   | HV   | High Voltage | Pink       |
| 2   | HV   | High Voltage | White      |

Note (1) The backlight interface housing for high voltage side is a model BHR-04VS-1, manufactured by JST. The mating header on inverter part number is SM02(12.0)B-BHS-1-TB(LF).





**5.3 INVERTER UNIT**

CN1: S12B-PH-SM3-TB(D)(LF)(JST) or equivalent

| Pin № | Symbol | Feature                     |
|-------|--------|-----------------------------|
| 1     | VBL    | +24V                        |
| 2     |        |                             |
| 3     |        |                             |
| 4     |        |                             |
| 5     |        |                             |
| 6     | GND    | GND                         |
| 7     |        |                             |
| 8     |        |                             |
| 9     |        |                             |
| 10    |        |                             |
| 11    | I_PWM  | Internal PWM Control Signal |
| 12    | BLON   | BL ON/OFF                   |

CN2: S12B-PH-SM3-TB(D)(LF)(JST) or equivalent

| Pin № | Symbol | Feature |
|-------|--------|---------|
| 1     | VBL    | +24V    |
| 2     |        |         |
| 3     |        |         |
| 4     |        |         |
| 5     |        |         |
| 6     | GND    | GND     |
| 7     |        |         |
| 8     |        |         |
| 9     |        |         |
| 10    |        |         |
| 11    | NC     | NC      |
| 12    | NC     | NC      |

CN3-CN18: SM02(12.0)B-BHS-1-TB(LF)(JST) or equivalent

| Pin № | Symbol   | Description       |
|-------|----------|-------------------|
| 1     | CCFL HOT | CCFL high voltage |
| 2     | CCFL HOT | CCFL high voltage |



CN23-CN26: 528521070 (Molex)


| Pin № | Symbol         | Description    |
|-------|----------------|----------------|
| 1     | Control Signal | Board to Board |
| 2     |                | Board to Board |
| 3     |                | Board to Board |
| 4     |                | Board to Board |
| 5     |                | Board to Board |
| 6     |                | Board to Board |
| 7     |                | Board to Board |
| 8     |                | Board to Board |
| 9     |                | Board to Board |
| 10    |                | Board to Board |

CN27: 528520870 (Molex)

| Pin № | Symbol         | Description    |
|-------|----------------|----------------|
| 1     | Control Signal | Board to Board |
| 2     |                | Board to Board |
| 3     |                | Board to Board |
| 4     |                | Board to Board |
| 5     |                | Board to Board |
| 6     |                | Board to Board |
| 7     |                | Board to Board |
| 8     |                | Board to Board |

Note (1) Floating of any control signal is not allowed.

## 5.4 BLOCK DIAGRAM OF INTERFACE



R0~R7: Pixel R data

G0~G7: Pixel G data

B0~B7: Pixel B data

DE: Data enable signal

DCLK: Data clock signal

Note (1) The system must have the transmitter to drive the module.

Note (2) LVDS cable impedance shall be 50 ohms per signal line or about 100 ohms per twist-pair line when it is used differentially.

## 5.5 LVDS INTERFACE

|           | SIGNAL                 |                 | TRANSMITTER<br>THC63LVDM83<br>A |          | INTERFACE CONNECTOR      |                        | RECEIVER<br>THC63LVDF84A |              | TFT CONTROL INPUT      |                 |
|-----------|------------------------|-----------------|---------------------------------|----------|--------------------------|------------------------|--------------------------|--------------|------------------------|-----------------|
|           | LVDS_SEL<br>=L or OPEN | LVDS_SEL<br>= H | PIN                             | INPUT    | Host                     | TFT-LCD                | PIN                      | OUTPUT       | LVDS_SEL<br>=L or OPEN | LVDS_SEL<br>= H |
| 24<br>bit | R0                     | R2              | 51                              | TxIN0    | TA OUT0+                 | Rx 0+                  | 27                       | Rx OUT0      | R0                     | R2              |
|           | R1                     | R3              | 52                              | TxIN1    |                          |                        | 29                       | Rx OUT1      | R1                     | R3              |
|           | R2                     | R4              | 54                              | TxIN2    |                          |                        | 30                       | Rx OUT2      | R2                     | R4              |
|           | R3                     | R5              | 55                              | TxIN3    |                          |                        | 32                       | Rx OUT3      | R3                     | R5              |
|           | R4                     | R6              | 56                              | TxIN4    | TA OUT0-                 | Rx 0-                  | 33                       | Rx OUT4      | R4                     | R6              |
|           | R5                     | R7              | 3                               | TxIN6    |                          |                        | 35                       | Rx OUT6      | R5                     | R7              |
|           | G0                     | G2              | 4                               | TxIN7    |                          |                        | 37                       | Rx OUT7      | G0                     | G2              |
|           | G1                     | G3              | 6                               | TxIN8    |                          |                        | 38                       | Rx OUT8      | G1                     | G3              |
|           | G2                     | G4              | 7                               | TxIN9    | TA OUT1+                 | Rx 1+                  | 39                       | Rx OUT9      | G2                     | G4              |
|           | G3                     | G5              | 11                              | TxIN12   |                          |                        | 43                       | Rx OUT12     | G3                     | G5              |
|           | G4                     | G6              | 12                              | TxIN13   |                          |                        | 45                       | Rx OUT13     | G4                     | G6              |
|           | G5                     | G7              | 14                              | TxIN14   |                          |                        | 46                       | Rx OUT14     | G5                     | G7              |
|           | B0                     | B2              | 15                              | TxIN15   | TA OUT1-                 | Rx 1-                  | 47                       | Rx OUT15     | B0                     | B2              |
|           | B1                     | B3              | 19                              | TxIN18   |                          |                        | 51                       | Rx OUT18     | B1                     | B3              |
|           | B2                     | B4              | 20                              | TxIN19   |                          |                        | 53                       | Rx OUT19     | B2                     | B4              |
|           | B3                     | B5              | 22                              | TxIN20   |                          |                        | 54                       | Rx OUT20     | B3                     | B5              |
|           | B4                     | B6              | 23                              | TxIN21   | TA OUT2+                 | Rx 2+                  | 55                       | Rx OUT21     | B4                     | B6              |
|           | B5                     | B7              | 24                              | TxIN22   |                          |                        | 1                        | Rx OUT22     | B5                     | B7              |
|           | DE                     | DE              | 30                              | TxIN26   |                          |                        | 6                        | Rx OUT26     | DE                     | DE              |
|           | R6                     | R0              | 50                              | TxIN27   | TA OUT2-                 | Rx 2-                  | 7                        | Rx OUT27     | R6                     | R0              |
|           | R7                     | R1              | 2                               | TxIN5    |                          |                        | 34                       | Rx OUT5      | R7                     | R1              |
|           | G6                     | G0              | 8                               | TxIN10   |                          |                        | 41                       | Rx OUT10     | G6                     | G0              |
|           | G7                     | G1              | 10                              | TxIN11   |                          |                        | 42                       | Rx OUT11     | G7                     | G1              |
|           | B6                     | B0              | 16                              | TxIN16   | TA OUT3+                 | Rx 3+                  | 49                       | Rx OUT16     | B6                     | B0              |
|           | B7                     | B1              | 18                              | TxIN17   |                          |                        | 50                       | Rx OUT17     | B7                     | B1              |
|           | RSVD 1                 | RSVD 1          | 25                              | TxIN23   |                          |                        | 2                        | Rx OUT23     | NC                     | NC              |
|           | RSVD 2                 | RSVD 2          | 27                              | TxIN24   | TA OUT3-                 | Rx 3-                  | 3                        | Rx OUT24     | NC                     | NC              |
|           | RSVD 3                 | RSVD 3          | 28                              | TxIN25   |                          |                        | 5                        | Rx OUT25     | NC                     | NC              |
| DCLK      |                        |                 | 31                              | TxCLK IN | TxCLK OUT+<br>TxCLK OUT- | RxCLK IN+<br>RxCLK IN- | 26                       | RxCLK<br>OUT | DCLK                   |                 |

R0~R7: Pixel R Data (7; MSB, 0; LSB)

G0~G7: Pixel G Data (7; MSB, 0; LSB)

B0~B7: Pixel B Data (7; MSB, 0; LSB)

DE : Data enable signal

DCLK : Data clock signal

Notes: (1) RSVD (reserved) pins on the transmitter shall be "H" or "L".

## 5.6 COLOR DATA INPUT ASSIGNMENT

The brightness of each primary color (red, green and blue) is based on the 8-bit gray scale data input for the color.

The higher the binary input, the brighter the color. The table below provides the assignment of the color versus data input.

| Color            |                  | Data Signal |    |    |    |    |    |    |    |       |    |    |    |    |    |    |    |      |    |    |    |    |    |    |    |
|------------------|------------------|-------------|----|----|----|----|----|----|----|-------|----|----|----|----|----|----|----|------|----|----|----|----|----|----|----|
|                  |                  | Red         |    |    |    |    |    |    |    | Green |    |    |    |    |    |    |    | Blue |    |    |    |    |    |    |    |
|                  |                  | R7          | R6 | R5 | R4 | R3 | R2 | R1 | R0 | G7    | G6 | G5 | G4 | G3 | G2 | G1 | G0 | B7   | B6 | B5 | B4 | B3 | B2 | B1 | B0 |
| Basic Colors     | Black            | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Red              | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Green            | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Blue             | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
|                  | Cyan             | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1    | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
|                  | Magenta          | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
|                  | Yellow           | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1     | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | White            | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1     | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 1    | 1  | 1  | 1  | 1  | 1  | 1  | 1  |
| Red Gray Scale   | Red (0) / Dark   | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Red (1)          | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Red (2)          | 0           | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | Red (253)        | 1           | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Red (254)        | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Red (255)        | 1           | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
| Green Gray Scale | Green (0) / Dark | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Green (1)        | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Green (2)        | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 1  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | Green (253)      | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1     | 1  | 1  | 1  | 1  | 1  | 0  | 1  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Green (254)      | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1     | 1  | 1  | 1  | 1  | 1  | 1  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Green (255)      | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 1  | 1     | 1  | 1  | 1  | 1  | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
| Blue Gray Scale  | Blue (0) / Dark  | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 0  |
|                  | Blue (1)         | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0  | 0  | 1  |
|                  | Blue (2)         | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 1  | 0  | 0  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | :                | :           | :  | :  | :  | :  | :  | :  | :  | :     | :  | :  | :  | :  | :  | :  | :  | :    | :  | :  | :  | :  | :  | :  | :  |
|                  | Blue (253)       | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1  | 1  | 0  | 1  |
|                  | Blue (254)       | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1  | 1  | 1  | 0  |
|                  | Blue (255)       | 0           | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1  | 1  | 1  | 1  |

Note (1) 0: Low Level Voltage, 1: High Level Voltage

## 6. INTERFACE TIMING


### 6.1 INPUT SIGNAL TIMING SPECIFICATIONS

The input signal timing specifications are shown as the following table and timing diagram.

| Signal                         | Item                        | Symbol | Min. | Typ. | Max. | Unit | Note       |
|--------------------------------|-----------------------------|--------|------|------|------|------|------------|
| LVDS Receiver Clock            | Frequency                   | 1/Tc   | 60   | 86   | 88   | MHZ  | -          |
|                                | Input cycle to cycle jitter | Trcl   | -    | -    | 200  | ps   | -          |
| LVDS Receiver Data             | Setup Time                  | Tlvsu  | 600  | -    | -    | ps   | -          |
|                                | Hold Time                   | Tlvhd  | 600  | -    | -    | ps   | -          |
| Vertical Active Display Term   | Frame Rate                  |        | 57   | 60   | 63   | Hz   |            |
|                                | Total                       | Tv     | 778  | 795  | 888  | Th   | Tv=Tvd+Tvb |
|                                | Display                     | Tvd    | 768  | 768  | 768  | Th   | -          |
|                                | Blank                       | Tvb    | 10   | 27   | 120  | Th   | -          |
| Horizontal Active Display Term | Total                       | Th     | 1442 | 1798 | 1936 | Tc   | Th=Thd+Thb |
|                                | Display                     | Thd    | 1366 | 1366 | 1366 | Tc   | -          |
|                                | Blank                       | Thb    | 76   | 432  | 570  | Tc   | -          |

Note : Since the module is operated in DE only mode, Hsync and Vsync input signals should be set to low logic level. Otherwise, this module would operate abnormally.

### INPUT SIGNAL TIMING DIAGRAM






**CHI MEI**  
OPTOELECTRONICS CORP.

Issue Date: Sep.22.2007

Model No.: V420B1-L01

**Approval**

### LVDS INPUT INTERFACE TIMING DIAGRAM





**CHI MEI**  
OPTOELECTRONICS CORP.


Issue Date: Sep.22.2007  
Model No.: V420B1-L01

**Approval**

## 6.2 POWER ON/OFF SEQUENCE

To prevent a latch-up or DC operation of LCD module, the power on/off sequence should follow the diagram below.

### POWER ON/OFF SEQUENCE



Note.

The supply voltage of the external system for the module input should follow the definition of Vcc.

Apply the lamp voltage within the LCD operation range. When the backlight turns on before the LCD operation or the LCD turns off before the backlight turns off, the display may momentarily become abnormal screen.

In case of VCC is in off level, please keep the level of input signals on the low or high impedance.

T4 should be measured after the module has been fully discharged between power off and on period.

Interface signal shall not be kept at high impedance when the power is on.



## 7. OPTICAL CHARACTERISTICS

### 7.1 TEST CONDITIONS

| Item                             | Symbol                                                        | Value   | Unit |
|----------------------------------|---------------------------------------------------------------|---------|------|
| Ambient Temperature              | Ta                                                            | 25±2    | °C   |
| Ambient Humidity                 | Ha                                                            | 50±10   | %RH  |
| Supply Voltage                   | VCC                                                           | 12      | V    |
| Input Signal                     | According to typical value in "3. ELECTRICAL CHARACTERISTICS" |         |      |
| Lamp Current                     | IL                                                            | 6.5±0.5 | mA   |
| Oscillating Frequency (Inverter) | FW                                                            | 50±3    | KHz  |
| Vertical Frame Rate              | Fr                                                            | 60      | Hz   |


### 7.2 OPTICAL SPECIFICATIONS

The relative measurement methods of optical characteristics are shown in 7.2. The following items should be measured under the test conditions described in 7.1 and stable environment shown in Note (6).

| Item                      |             | Symbol        | Condition                                                                 | Min.          | Typ.  | Max.          | Unit              | Note     |
|---------------------------|-------------|---------------|---------------------------------------------------------------------------|---------------|-------|---------------|-------------------|----------|
| Contrast Ratio            |             | CR            | $\theta_x=0^\circ, \theta_y=0^\circ$<br>Viewing angle at normal direction | 1200          | 1500  |               | -                 | Note (2) |
|                           |             | Dynamic CR    |                                                                           |               | 6000  |               |                   |          |
| Response Time             |             | Gray to gray  |                                                                           |               | 6.5   | 12            | ms                | Note (3) |
| Center Luminance of White |             | LC            |                                                                           | 400           | 500   |               | cd/m <sup>2</sup> | Note (4) |
| White Variation           |             | $\delta W$    |                                                                           |               |       | 1.3           | -                 | Note (7) |
| Cross Talk                |             | CT            |                                                                           |               |       | 4             | %                 | Note (5) |
| Color Chromaticity        | Red         | Rx            |                                                                           | Typ.<br>-0.03 | 0.644 | Typ.<br>+0.03 | -                 | Note (6) |
|                           |             | Ry            |                                                                           |               | 0.333 |               | -                 |          |
|                           | Green       | Gx            |                                                                           |               | 0.272 |               | -                 |          |
|                           |             | Gy            |                                                                           |               | 0.591 |               | -                 |          |
|                           | Blue        | Bx            |                                                                           |               | 0.143 |               | -                 |          |
|                           |             | By            |                                                                           |               | 0.070 |               | -                 |          |
|                           | White       | Wx            |                                                                           |               | 0.280 |               | -                 |          |
|                           |             | Wy            |                                                                           |               | 0.285 |               | -                 |          |
|                           | Color Gamut | C.G           |                                                                           |               | 72    |               | %                 | NTSC     |
| Viewing Angle             | Horizontal  | $\theta_{x+}$ | CR≥20                                                                     | 80            | 88    |               | Deg.              | Note (1) |
|                           |             | $\theta_{x-}$ |                                                                           | 80            | 88    |               |                   |          |
|                           | Vertical    | $\theta_{Y+}$ |                                                                           | 80            | 88    |               |                   |          |
|                           |             | $\theta_{Y-}$ |                                                                           | 80            | 88    |               |                   |          |

Note (1) Definition of Viewing Angle ( $\theta_x$ ,  $\theta_y$ ):

Viewing angles are measured by Eldim EZ-Contrast 160R



Note (2) Definition of Contrast Ratio (CR):

The contrast ratio can be calculated by the following expression.


Surface Luminance with all white pixels

$$\text{Contrast Ratio (CR)} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

CR = CR (5), where CR (X) is corresponding to the Contrast Ratio of the point X at the figure in Note (7).

The measured value will be "Dynamic CR" only when the function of dynamic contrast ratio is enabled.

Note (3) Definition of Gray-to-Gray Switching Time:

**Optical Response**

The driving signal means the signal of gray level 0, 63, 127, 191, and 255.

Gray to gray average time means the average switching time of gray level 0, 63, 127, 191, 255 to each other.

Note (4) Definition of Luminance of White (LC, LAVE):

Measure the luminance of gray level 255 at center point and 5 points

LC = L (5), where L (X) is corresponding to the luminance of the point X at the figure in Note (7).


Note (5) Definition of Cross Talk (CT):

$$CT = |Y_B - Y_A| / Y_A \times 100 (\%)$$

Where:


YA = Luminance of measured location without gray level 0 pattern (cd/m<sup>2</sup>)

YB = Luminance of measured location with gray level 0 pattern (cd/m<sup>2</sup>)



Note (6) Measurement Setup:


The LCD module should be stabilized at given temperature for 1 hour to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting backlight for 1 hour in a windless room.



Note (7) Definition of White Variation ( $\delta W$ ):

Measure the luminance of gray level 255 at 5 points

$$\delta W = \text{Maximum} [L(1), L(2), L(3), L(4), L(5)] / \text{Minimum} [L(1), L(2), L(3), L(4), L(5)]$$



## 8. PRECAUTIONS

### 8.1 ASSEMBLY AND HANDLING PRECAUTIONS

- [ 1 ] Do not apply rough force such as bending or twisting to the module during assembly.
- [ 2 ] It is recommended to assemble or to install a module into the user's system in clean working areas. The dust and oil may cause electrical short or worsen the polarizer.
- [ 3 ] Do not apply pressure or impulse to the module to prevent the damage of LCD panel and Backlight.
- [ 4 ] Always follow the correct power-on sequence when the LCD module is turned on. This can prevent the damage and latch-up of the CMOS LSI chips.
- [ 5 ] Do not plug in or pull out the I/F connector while the module is in operation.
- [ 6 ] Do not disassemble the module.
- [ 7 ] Use a soft dry cloth without chemicals for cleaning, because the surface of polarizer is very soft and easily scratched.
- [ 8 ] Moisture can easily penetrate into LCD module and may cause the damage during operation.
- [ 9 ] When storing modules as spares for a long time, the following precaution is necessary.
  - [ 9.1 ] Do not leave the module in high temperature, and high humidity for a long time. It is highly recommended to store the module with temperature from 0 to 35°C at normal humidity without condensation.
  - [ 9.2 ] The module shall be stored in dark place. Do not store the TFT-LCD module in direct sunlight or fluorescent light.
- [ 10 ] When ambient temperature is lower than 10°C, the display quality might be reduced. For example, the response time will become slow, and the starting voltage of CCFL will be higher than that of room temperature.


### 8.2 SAFETY PRECAUTIONS

- [ 1 ] The startup voltage of a Backlight is approximately 1000 Volts. It may cause an electrical shock while assembling with the inverter. Do not disassemble the module or insert anything into the Backlight unit.
- [ 2 ] If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.
- [ 3 ] After the module's end of life, it is not harmful in case of normal operation and storage.

## 9. DEFINITION OF LABELS

### 9.1 CMO MODULE LABEL


The barcode nameplate is pasted on each module as illustration, and its definitions are as following explanation.



Model Name: V420B1-L01

Revision: Rev. XX, for example: A0, A1... B1, B2... or C1, C2...etc.

Serial ID: X X X X X X Y M D L N N N N



Serial ID includes the information as below:

Manufactured Date:

Year: 0~9, for 2000~2009

Month: 1~9, A~C, for Jan. ~ Dec.

Day: 1~9, A~Y, for 1st to 31st, exclude I, O, and U.

Revision Code: Cover all the change

Serial No.: Manufacturing sequence of product

Product Line: 1 -> Line1, 2 -> Line 2, ...etc.

## 10. PACKAGING

### 10.1 PACKAGING SPECIFICATIONS


3 LCD TV modules / 1 Box

Box dimensions: 1080(L) X 282 (W) X 685(H)

Weight: approximately 45Kg (3 modules per box)

### 10.2 PACKAGING METHOD

Figures 10-1 and 10-2 are the packing method.



## Sea / Land Transportation (40ft HQ Container)



Air Transportation &  
Sea / Land Transportation (40ft Container)

Figure.10-2 Packing method




**CHI MEI**  
OPTOELECTRONICS CORP.


Issue Date: Sep.22.2007

Model No.: V420B1-L01

**Approval**

## 11. MECHANICAL CHARACTERISTICS





**CHI MEI**  
OPTOELECTRONICS CORP.

Issue Date: Sep.22.2007

Model No.: V420B1-L01

**Approval**